

Residential ESS Battery - Wall Mounted

Hi-WALL 5

5.12kWh (51.2V)

52kg 468 × 542 × 197 mm



High Performance

- 90% usable energy
- 70A continuous discharging current
- Long lifespan

Flexibility

- Modular design
- Extendable during lifetime
- Support 1-4 modules in parallel

Safety

- Lithium iron phosphate battery
- Multi-stages protection design

Easy Installation

- Compact Design
- Plug and Play



Specifications

Model	Hi-WALL 5
Physical	
Battery Type	LFP (LiFePO4)
Cell Manufacturer	 Gotion
System Weight	52KG
Dimension (W x D x H)	468 x 542 x 197 mm
IP Protection	IP54
Warranty	10 Years
Electrical	
Energy Capacity	5.12 kWh
Usable Capacity	4.60 kWh
Depth of Discharge (DoD)	90%
Nominal Voltage	51.2V
Operating Voltage Range	48 ~ 57.6V
Internal Resistance	≤ 30 mΩ
Cycle Life	6000 @ 0.5C 25°C*
Operation	
Max. Charging/Discharging Current	70 A (0.7C) / 100 A (1C)
Recommended Charging/Discharging Current	50 A (0.5C) / 70 A (0.7C)
Max. Charging/Discharging Power	3584W / 5120W
Max. Short-circuit Current Operating	150 A
Temperature Range	-10 °C ~ 50 °C**, 0 °C ~ 40 °C
Humidity	15% ~ 85%
BMS	
Modules Connection	1 ~ 4 in parallel
Capacity	5.12 / 10.24 / 15.36 / 20.48 kWh
Usable Capacity	4.60 / 9.20 / 13.80 / 18.40 kWh
Power Consumption	< 2 W (Work), < 100 mW (Sleep)
Communication	CAN and RS-485 compatible
Certification	
Transportation	UN 38.3
Safety	IEC 62619 (Cell)

* Under specific test conditions

** When the temperature is below 0°C or above 40°C, the performance will be limited.



WhatsApp: +86 15021028508



www.hiwotech.com



sales@hiwotech.com