

SMART AC Charging Station

Hi-Charger 7kW AC Charging Station

Easy To Use
Durable
Safe and reliable



Shape Smart, Inner Smart

- Fashion, Breathing lamps, A4 size, Stylish, 7 status 7 color lights indication

PC alloy charging pile (ABS+ PC alloy)

- Impact resistance, high gloss, high hardness, high cost performance, lightweight

Scram button Air switch

- Scram button and air switch available to deal with possible emergencies

Anti-ultraviolet outside, flame retardant inside

Specifications

SMART AC charging pile

Basic parameters		Electrical part	
Specifications & dimensions	315*215*78mm	Rated voltage	230V
Working temperature	-20°C ~ +50°C	Rated current	16/32A
Relative humidity	5%~95%	Rated frequency	50Hz
Protection grade	IP54	Altitude	≤2000M

Functional parameter		Protection function	
Charging mode	automatic	Protection function	Over-voltage, under-voltage, short-circuit, overload and electric leakage
State display	Red, green and yellow LED indicators	Rated operating current of residual current protection	≤30mA
User authentication	RFID card, remote control	Rated operating time of residual current protection	≤0.1s
Product standard	IEC 61851	Mechanical operation life of charging linker	≥10,000



WhatsApp: +86 15021028508



www.hiwotech.com



sales@hiwotech.com